

# Gyprock® Product Datasheet



## Gyprock Ultra-Top™

Gyprock Ultra-Top is a premium, lightweight topping compound used as a topping coat in a three coat plasterboard jointing system.

Ultra-Top is ultra-light to mix and apply, ultra-creamy for excellent spreadability and ultra-easy to sand for an ultra-smooth finish.

Ultra-Top is a low VOC, pre-mixed compound, manufactured by Gyprock in Australia to stringent product specifications and is packed in a black coloured bucket.



### Topping Coat

Ultra-Top has superior coverage and its ultra-light and creamy consistency makes mixing and application simple with effortless sanding for an ultra-smooth finish.



### Hand and Machine Tool Applied

Gyprock Ultra-Top features advanced trowelability and is easy to apply with hand tools or finishing boxes.

## Product Options

Gyprock Ultra-Top is available in pre-mixed form in a 15kg (approx. 14L) pail.

## Application

### Hand Tools

1. Allow adequate time for the second coat to harden before applying the Ultra-Top final coat.
2. Using a 250mm or 300mm broadknife, apply a thin topping coat of Ultra-Top wide enough to conceal the previously coated joint. Soften the outer edges of the newly trowelled compound with a damp brush before feathering the edges with a trowel.
3. Using a 100mm broadknife, cover previously coated fastener heads, overlapping about 25mm.

### Machine Tools

Apply a thin coat of Ultra-Top using a 250mm or 300mm finishing box.

### Sanding

Allow Ultra-Top to dry for at least 24 hours, then sand to a smooth finish using 180 grit sandpaper or 180-220 grit sanding mesh.

# More Installation Assistance

Comprehensive installation instructions for Gyprock plasterboard and compounds can be found under the [Resources](#) tab and include:

- [DIY installation guides](#)
- [DIY installation videos](#)
- [Professional installation guides](#)

For assistance with installation, try searching for a [Gyprock plasterer](#), [builder](#) or [repairer](#) under the [Locations](#) tab.

Product Availability			
Weight	Pack	Coverage-Approx Qty/100m <sup>2</sup>	Shelf Life
15kg (approx. 14L)	Black pail	5.5L	1 year from manufacture

To confirm product availability, please check with your local [Gyprock supplier](#), or contact [Gyprock customer service](#)

## Product Manufacture

Gyprock Ultra-Top is manufactured by Gyprock in Australia to stringent product specifications.

## Plasterboard Installation

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

## Levels of Finish

A Level of Finish sets out the minimum specifications for installation processes from framing preparation to painting and decoration. The levels are defined in AS/NZS 2589.1, and are intended to provide builders, installers and homeowners with defined methods and practices necessary to meet expectations in terms of the Level of Finish.

The level of finish should be specified prior to construction as it can be affected at different stages of construction and tolerances must be adhered to:

- Frame construction
- Plasterboard fixing and backblocking
- Plasterboard jointing and setting

A Level 3 Finish is for areas that do not require painting and decoration such as above ceilings and inside service shafts.

A Level 4 Finish is the generally accepted level for domestic construction

A level 5 Finish should be specified wherever gloss, semi-gloss or dark coloured paints are to be used, or where critical glancing light conditions are likely.

More information on Levels of Finish can be found in the [Gyprock Residential Installation Guide](#)

# Painting and Decoration

Finishes applied to plasterboard surfaces can have a significant effect on the perceived quality of the installation, particularly where critical lighting conditions exist.

- Textured or heavy patterned finishes tend to hide imperfections
- Matt finishes minimise imperfection visibility
- Semi-gloss and gloss finishes highlight imperfections
- Light colours are less likely to show imperfections and impact damage

Gyprock recommends paint systems consisting of one coat of a plasterboard sealer followed by two coats of finishing paint. Always follow the manufacturer's instructions for application and recoating.

Gyprock recommends decoration in line with [Master Painters Australia](#).

Physical and chemical properties	
Specific gravity (H <sub>2</sub> O=1)	1.0 – 1.4
VOC content (as specified by GBCA)	<1 gram per Litre as VOC content per material

Ingredients	
Calcium Carbonate	
Talc	
Perlite	
Clay	
Ethylene vinyl acetate polymer emulsion	
Water	

## Material Safety

### MSDS

A [Material Safety Data Sheet](#) for Gyprock Ultra-Top is available from the Gyprock website under the [Resources](#) tab.

### Handling and storage

For guidelines on the safe handling of Gyprock products, reference should be made to the Gypsum Board Manufacturers of Australasia (GBMA) publication *“Move it the GBMA Way – A Safe Manual Handling Guide for the Plasterboard Industry – Training Guide”* (Reference SS172).

This product should be stored in its factory packaging in a dry area.



Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system



**Low VOC**

All Gyprock jointing products exceed the GBCA specification for Volatile Organic Compound content according to independent testing. Test certificates are available under the [Resources](#) tab.



GYP-2014  
AFSV4.0-2014  
Adhesives, Fillers & Sealants

Gyprock Ultra-Top™ is accredited to the GECA AFSV4.0-2014 Adhesives, Fillers & Sealants Standard which is compliant with the requirements of the GBCA's Assessment Framework for product certification schemes.