

Gyprock® Product Datasheet



Gyprock® Wet Area Acrylic Sealant

Gyprock Wet Area Acrylic Sealant is a paintable, permanently flexible sealant designed to seal the edges of Gyprock Aquachek against pre-formed shower bases, baths and around plumbing penetrations.

It can also be used as a general purpose gap filler, providing mould and mildew resistance.

It is a low VOC acrylic compound manufactured to stringent product specifications and packed in a purple and white caulking gun tube.

Product Options

Wet Area Acrylic Sealant is available in a 450g tube.

Installation

Comprehensive installation instructions for Gyprock plasterboard cornice and compounds can be found under the [Resources](#) tab and include:

- [DIY installation guides](#)
- [DIY installation videos](#)
- [Professional installation guides](#)

For assistance with installation, try searching for a [Gyprock plasterer](#), [builder](#) or [repairer](#) under the [Locations](#) tab.

Product availability		
Weight	Pack	Shelf Life
450g	Purple and white tube	1 year from manufacture

Physical and chemical properties	
Specific gravity (H ₂ O=1)	Approximately 1.55
VOC content	Trace

Ingredients	
Acrylic emulsion	
Butyl acrylate-styrene co-polymer	
Inert fillers	

To confirm product availability, please check with your local [Gyprock supplier](#), or contact [Gyprock customer service](#)

Material Safety

MSDS

A [Material Safety Data Sheet](#) for Gyprock Wet Area Acrylic Sealant is available from the Gyprock website under the [Resources](#) tab.

Handling and storage

For guidelines on the safe handling of Gyprock products, reference should be made to the Gypsum Board Manufacturers of Australasia (GBMA) publication *“Move it the GBMA Way – A Safe Manual Handling Guide for the Plasterboard Industry – Training Guide”* (Reference SS172).

This product should be stored in its factory packaging in a dry area.



Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system



Low VOC

All Gyprock jointing products exceed the GBCA specification for Volatile Organic Compound content according to independent testing. Test certificates are available under the [Resources](#) tab.